Fulham FIREHORSE EMERGENCY BALLAST

SLL = Selectable Lamp Leads

SELF-DIAGNOSTIC SPECIFICATION CROSS REFERENCE

Mfg/Model	Lumen Range	E-time Minutes	E-mode #Lamps		Input Voltage		UL Rating Location		Case Construction		Case Dimension			Advanced Features				Temp. Range	Lamp Special	Battery Rating	
	Avg. Initial Lumens	90	One	Two	Dual	Unv.	Dry	Damp	Paint	Galv.	Length Inches	Width Inches	Height Inches	Selectable Audible or Color LED	Dual Audible & LED	Remote Test	SLL	0-55c	T5HO	ACInput Watts	Wh
FIREHORSE																					
No Models																					
Bodine																					
*B30ST	1800-3500	•	•	•	•			•	•		16.3	5.5	1.7	•				0-40c		8.0	57.6
B35ST	1800-3000	•	•		•			•	•		16.3	5.5	1.7	•				0-40c	•	8.0	57.6
*B50ST	1100-1400	•	•	•	•		•		•		13.3	2.4	1.5	•				•		4.0	24.0
*B50CHIC	1100-1400	•	•	•	•		•		•		13.3	2.4	1.5		•			•		4.0	24.0
LP600STU	600-1325	•	•			•		•		•	22.5	1.18	1.18	•				0-50c	•	5.0	18.5
*B74CST	350-1000	•	•	•	•		•		•		13.3	2.4	1.5	•				•		3.5	19.2
*B30RCT	1450-3500	•	•	•	•		•		•		16.3	5.5	1.7			•		NL		8.0	57.6
*B50RCT	1100-1400	•	•	•	•		•		•		13.3	2.4	1.5			•		•		4.0	24.0
RCT-A-**C	select models	•			•		•	•		•	8.0	1.2	1.15			Retro-Module				.26/1.4	
B50FEBNET	1100-1400	•	•	•	•		•		•		13.3	2.4	1.5	•		•		•		4.0	24.0
Chicago approval																					
*single flex whip																					
Iota																					
ISD80/DL	680-1300	•	•	•		•	•	•	•		13.0	2.2	1.5		•		•	•		3.5	24.0
ISD420EMA/DL	600-1300	•	•	•		•	•	•	•		13.1	2.4	1.5		•		•	•		4.0	24.0
SD420EMB/DL	600-1300	•	•	•		•	•	•	•		13.1	2.4	1.5		•		•	•		4.0	24.0
dual flex whip & plate																					
SD80 Chicago Approval																					