



SLL = Selectable Lamp Leads

LOW PROFILE SPECIFICATION CROSS REFERENCE

Mfg/Model	Lumen Range	E-time Minutes	E-mode #Lamps		Input Voltage		UL Rating Location		Case Construction		Case Dimension			Test Switch / LED Indicator		Advanced Features		Temperature Range		Battery Rating	
			90	One	Two	Dual	Dry	Damp	Paint	Galv.	Length Inches	Width Inches	Height Inches	Single	Dual	T5HO	SLL	0-50c	0-55c	AC Input Watts	Wh
FIREHORSE																					
FH7	400-500	•	•		•		•		•		9.8	2.25	1.13	•			•			2.5	9.0
FH8	700-1300	•	•	•	•		•		•		21.5	1.18	1.15	•		•	•	•		2.5	21.0
FH9	400-800	•	•		•		•		•		17.5	1.18	1.15	•		•	•	•		2.5	15.0
FH10	320-500	•	•		•		•		•		14.2	1.18	1.15	•			•	•		2.5	9.0
Bodine																					
*B50LP	750-1300	•	•	•	•		•		•		21.5	1.18	1.18		•			•		4.0	21.0
*LP600	600-1325	•	•		•		•		•		21.5	1.18	1.18		•	•		•	•	3.0	18.5
*LP550	390-700	•	•		•	•			•		18.5	1.18	1.18		•	•			•	2.6	13.2
*LP500	400-520	•	•		•	•			•		18.5	1.18	1.0		•			•		1.5	10.8
*LP400	450	•	•		•	•			•		14.1	1.5	1.0		•			•		1.5	7.2
*Chicago Approval																					
Iota																					
ISL28/DL	320-500	•	•		•	•	•		•		14.2	1.18	1.15	•			•		•	2.5	NL
ISL54/DL	450-825	•	•		•	•	•		•		17.5	1.18	1.15	•		•		•		2.5	24.0
ISL540/DL	700-1300	•	•		•	•	•		•		21.5	1.18	1.15	•		•		•		3.5	24.0
I32	425-500	•	•		•	•			•		9.5	2.0	1.0	•			•		•	2.5	NL
I320/DL	680-1400	•	•	•	•	•	•		•		13.0	2.2	1.15	•			•		•	3.5	24.0
ISL54035W	1300	•	•		•	•	•		•		21.5	1.18	1.15	•				•		3.5	24.0